

**3M™ FASARA™ DECORATIVE GLASS FINISHES — FROST/MATTE/METALLIC COLLECTION**

FASARA Frost/Matte/Metallic Collection — Spec Sheet & Warranty

3M FASARA Frost, Matte, and Metallic patterns are Guardian Bastille's most-requested decorative collection — from near-clear satin finishes to fully opaque privacy white and black. It includes the two FASARA patterns 3M rates for exterior-glazed use. Guardian Bastille installs this collection for restrooms, private offices, mirror backing, and any glazing needing full or partial opacity.

- Widest VLT range of any FASARA collection — from fully opaque (Silver 1, Opaque White) to a light satin frost (Fine Crystal, Oslo, Lausanne).
- Matte Crystal 2 and Milky Crystal are 3M-approved for exterior glazing in addition to interior use — see the warranty table below.

Performance Specifications (per 3M Technical Data Sheet)

Pattern	VLT %	Thickness
Chamonix	47%	4.7 mil (120 micron)
Essen	55%	4.7 mil (120 micron)
Fine Crystal	84%	4.4 mil (113 micron)
Glace	56%	3.3 mil (85 micron)
Lausanne	84%	4.4 mil (113 micron)
Luce	34%	3.3 mil (85 micron)
Mat Crystal-i	85%	3.7 mil (95 micron)
Mat Crystal 2	86%	5.0 mil (126 micron)
Milky Crystal	19%	5.0 mil (126 micron)
Milano (Milky White)	59%	3.0 mil (77 micron)
Oslo	83%	4.7 mil (119 micron)
Oslo for Plastic	—	—
San Marino (Milky White)	21%	4.1 mil (105 micron)
Silver 1	0%	2.9 mil (74 micron)
Transparent for Glace	—	—
Opaque White	10%	5.6 mil (142 micron)

Source: 3M™ FASARA™ Glass Finishes Technical Data Sheet and Product Bulletin (FASARA, January 2025). VLT and thickness values are 3M-published figures for each listed pattern. A dash (—) indicates the pattern is part of 3M's current FASARA collection but individual VLT/thickness data was not available in the referenced data table at time of publication — contact Guardian Bastille for current specifications on those variants.



Authorized Dealer Installer

Window Film Products

PRESTIGE DEALER NETWORK

Material, Application & Care (per 3M Technical Data Sheet)

- **Film Material** — Optically engineered polyester film (select patterns blend in polyvinyl chloride), with a silicone-coated polyester release liner.
- **Adhesive** — Pressure-sensitive acrylic, permanent, applied using 3M's wet application method to virtually eliminate air bubbles.
- **UV Rejection** — Blocks at least 99% of UV light.
- **Roll Format** — Standard 50 in. (127 cm) x 98.4 ft. (30 m) rolls; 60 in. and extended lengths available for select patterns.
- **Application Temperature** — 54°F to 100°F (12°C to 38°C) air and surface temperature; professional wet-glaze installation required on flat glass only.
- **Care** — Do not clean for 30 days after installation. Clean only with a soft, damp cloth or mild liquid detergent and water, wiping gently in one direction; never use ammonia, chlorine, organic solvents, or abrasive tools.



Commercial Warranty Coverage

Coverage	Term	Notes
Film Performance – Interior (Standard)	5 years	No cracking, crazing, delamination, bubbling, peeling, or discoloration under normal interior use
Film Performance – Interior, UV / Perimeter Exposure	3 years	Applies where direct UV or building-perimeter sun exposure accelerates wear
Removal & Reapplication Labor	1 year	Free labor to remove and reapply film if found defective under warranty
Film Performance – Exterior (Mat Crystal 2 & Milky Crystal only)	3 years	These two patterns are 3M-approved for exterior-glazed applications; all other patterns in this collection are interior-rated only

Requires professional wet-glaze installation by an authorized 3M dealer. FASARA Glass Finishes are designed for interior flat-glass applications; ask Guardian Bastille about exterior-rated pattern availability for your project.

→ [View 3M's official Technical Data Sheet: 3M FASARA Glass Finishes TDS](#)

→ [View 3M's official FASARA Product Bulletin](#)

Performance values above are transcribed from 3M's published Technical Data Sheet for this product and are provided for specification and bidding reference. Values are measured on 1/4" clear glass unless noted; actual field performance varies by glass type and installation. Consult the linked 3M documents for complete, current technical and warranty terms.

This guide is provided by Guardian Bastille, LLC for reference during specification and bidding. It does not modify or supersede 3M's published technical or warranty terms. Guardian Bastille is a 3M Prestige Dealer; this document does not represent 3M certification of any project.