



3M™ FASARA™ DECORATIVE GLASS FINISHES — GRADATION COLLECTION

FASARA Gradation Collection — Spec Sheet & Warranty

3M FASARA Gradation patterns shift smoothly from clear to frosted across the pane, softening sightlines without fully blocking them. Guardian Bastille installs the Gradation collection for conference rooms, private offices, and storefront glazing that wants a designed transition rather than a hard privacy line.

- Directional fade gives partial privacy while keeping natural light and a sense of openness on the clear side of the gradient.
- Available in a range of tones from near-transparent to heavily frosted — see the VLT column below for each pattern's light transmission.

Performance Specifications (per 3M Technical Data Sheet)

Pattern	VLT %	Thickness
Aerina	79%	3.2 mil (81 micron)
Illumina	—	—
Illumina Glace	—	—
Illumina Glace for Plastic	—	—
Illumina Silver	36%	3.0 mil (77 micron)
Lontano	61%	3.2 mil (81 micron)
Robe	—	—
Safu	—	—
Tsurugi	61%	3.2 mil (81 micron)
Venetian	54%	3.3 mil (85 micron)

Source: 3M™ FASARA™ Glass Finishes Technical Data Sheet and Product Bulletin (FASARA, January 2025). VLT and thickness values are 3M-published figures for each listed pattern. A dash (—) indicates the pattern is part of 3M's current FASARA collection but individual VLT/thickness data was not available in the referenced data table at time of publication — contact Guardian Bastille for current specifications on those variants.

Material, Application & Care (per 3M Technical Data Sheet)

- **Film Material** — Optically engineered polyester film (select patterns blend in polyvinyl chloride), with a silicone-coated polyester release liner.
- **Adhesive** — Pressure-sensitive acrylic, permanent, applied using 3M's wet application method to virtually eliminate air bubbles.
- **UV Rejection** — Blocks at least 99% of UV light.
- **Roll Format** — Standard 50 in. (127 cm) x 98.4 ft. (30 m) rolls; 60 in. and extended lengths available for select patterns.
- **Application Temperature** — 54°F to 100°F (12°C to 38°C) air and surface temperature; professional wet-glaze installation required on flat glass only.



Authorized Dealer Installer

Window Film Products

PRESTIGE DEALER NETWORK

-
- **Care** — Do not clean for 30 days after installation. Clean only with a soft, damp cloth or mild liquid detergent and water, wiping gently in one direction; never use ammonia, chlorine, organic solvents, or abrasive tools.



Commercial Warranty Coverage

Coverage	Term	Notes
Film Performance – Interior (Standard)	5 years	No cracking, crazing, delamination, bubbling, peeling, or discoloration under normal interior use
Film Performance – Interior, UV / Perimeter Exposure	3 years	Applies where direct UV or building-perimeter sun exposure accelerates wear
Removal & Reapplication Labor	1 year	Free labor to remove and reapply film if found defective under warranty

Requires professional wet-glaze installation by an authorized 3M dealer. FASARA Glass Finishes are designed for interior flat-glass applications; ask Guardian Bastille about exterior-rated pattern availability for your project.

→ [View 3M's official Technical Data Sheet: 3M FASARA Glass Finishes TDS](#)

→ [View 3M's official FASARA Product Bulletin](#)

Performance values above are transcribed from 3M's published Technical Data Sheet for this product and are provided for specification and bidding reference. Values are measured on 1/4" clear glass unless noted; actual field performance varies by glass type and installation. Consult the linked 3M documents for complete, current technical and warranty terms.

This guide is provided by Guardian Bastille, LLC for reference during specification and bidding. It does not modify or supersede 3M's published technical or warranty terms. Guardian Bastille is a 3M Prestige Dealer; this document does not represent 3M certification of any project.