



3M™ FASARA™ DECORATIVE GLASS FINISHES — STRIPE COLLECTION

FASARA Stripe Collection — Spec Sheet & Warranty

3M FASARA Stripe patterns use fine vertical banding to create a modern, architectural look — a popular choice for glass partitions and doors that need a code-compliant visual marker as well as privacy. Guardian Bastille installs the Stripe collection for offices, conference rooms, and interior storefronts.

- Vertical banding reads as a clean architectural line from a distance while still diffusing direct sightlines up close.
- Several patterns (Arpa Black, Shutie Black) offer a darker banded look for higher contrast against light-colored frames.

Performance Specifications (per 3M Technical Data Sheet)

Pattern	VLT %	Thickness
Arpa	67%	3.1 mil (79 micron)
Arpa Black	22%	3.2 mil (81 micron)
Fine	48%	3.2 mil (81 micron)
Nokto	—	—
Radius	—	—
Seattle	74%	3.2 mil (81 micron)
Seattle Fine	68%	3.1 mil (80 micron)
Shutie	59%	3.2 mil (81 micron)
Shutie Black	51%	3.2 mil (81 micron)

Source: 3M™ FASARA™ Glass Finishes Technical Data Sheet and Product Bulletin (FASARA, January 2025). VLT and thickness values are 3M-published figures for each listed pattern. A dash (—) indicates the pattern is part of 3M's current FASARA collection but individual VLT/thickness data was not available in the referenced data table at time of publication — contact Guardian Bastille for current specifications on those variants.

Material, Application & Care (per 3M Technical Data Sheet)

- **Film Material** — Optically engineered polyester film (select patterns blend in polyvinyl chloride), with a silicone-coated polyester release liner.
- **Adhesive** — Pressure-sensitive acrylic, permanent, applied using 3M's wet application method to virtually eliminate air bubbles.
- **UV Rejection** — Blocks at least 99% of UV light.
- **Roll Format** — Standard 50 in. (127 cm) x 98.4 ft. (30 m) rolls; 60 in. and extended lengths available for select patterns.
- **Application Temperature** — 54°F to 100°F (12°C to 38°C) air and surface temperature; professional wet-glaze installation required on flat glass only.
- **Care** — Do not clean for 30 days after installation. Clean only with a soft, damp cloth or mild liquid detergent and water, wiping gently in one direction; never use ammonia, chlorine, organic solvents, or abrasive tools.



Authorized Dealer Installer

Window Film Products

PRESTIGE DEALER NETWORK

Commercial Warranty Coverage

Coverage	Term	Notes
Film Performance – Interior (Standard)	5 years	No cracking, crazing, delamination, bubbling, peeling, or discoloration under normal interior use
Film Performance – Interior, UV / Perimeter Exposure	3 years	Applies where direct UV or building-perimeter sun exposure accelerates wear
Removal & Reapplication Labor	1 year	Free labor to remove and reapply film if found defective under warranty

Requires professional wet-glaze installation by an authorized 3M dealer. FASARA Glass Finishes are designed for interior flat-glass applications; ask Guardian Bastille about exterior-rated pattern availability for your project.

→ [View 3M's official Technical Data Sheet: 3M FASARA Glass Finishes TDS](#)

→ [View 3M's official FASARA Product Bulletin](#)

Performance values above are transcribed from 3M's published Technical Data Sheet for this product and are provided for specification and bidding reference. Values are measured on 1/4" clear glass unless noted; actual field performance varies by glass type and installation. Consult the linked 3M documents for complete, current technical and warranty terms.

This guide is provided by Guardian Bastille, LLC for reference during specification and bidding. It does not modify or supersede 3M's published technical or warranty terms. Guardian Bastille is a 3M Prestige Dealer; this document does not represent 3M certification of any project.