



Authorized Dealer Installer

Window Film Products

PRESTIGE DEALER NETWORK

3M™ SCOTCHSHIELD™ SAFETY & SECURITY WINDOW FILM

Ultra Prestige Series — Spec Sheet & Warranty

3M Scotchshield Ultra Prestige Series (S50) combines Ultra Series glass-retention performance with Prestige-level solar heat and glare control — one film for buildings that need both security glazing and energy performance. Guardian Bastille installs Ultra Prestige with wet-glaze and mechanical (IPA) structural attachment.

- Single film delivers both blast/impact glass retention and solar heat control.
- 3M security window film is designed to help hold glazing together on impact — it is not bulletproof and is not designed to stop intruders or prevent all property damage or injury.

Performance Specifications (per 3M Technical Data Sheet)

Specification	Ultra Prestige S50
Visible Light Transmission	49%
UV Transmission	<0.5%
Solar Heat Gain Coefficient	0.44
Total Solar Energy Rejected	56%
Vis. Light Reflection (Int. / Ext.)	7% / 8%
Nominal Thickness	8 mils (9.9 mils w/ adhesive)
Tensile Strength (MD / TD)	25,600 / 25,000 psi
Break Strength (MD / TD)	205 / 200 lb/in

Source: 3M Scotchshield Safety & Security Window Film Ultra Prestige S50 Technical Data Sheet. Measured on 1/4" clear glass per ASTM E903 (optical) and ASTM D882 (tensile/break strength).



Commercial Warranty Coverage

Coverage	Term	Notes
Glass Breakage	5 years*	Up to \$2,000/window, direct result of film application
Seal Failure	3 years	Insulated glass unit seal failure
Film Performance	10–12 years	Varies by installation and attachment system

*Requires professional installation by an authorized 3M window film dealer and warranty registration.

→ [View 3M's official Technical Data Sheet: 3M Scotchshield Ultra Prestige S50 TDS](#)

→ [View 3M's official Commercial Warranty Bulletin](#)

Performance values above are transcribed from 3M's published Technical Data Sheet for this product and are provided for specification and bidding reference. Values are measured on 1/4" clear glass unless noted; actual field performance varies by glass type and installation. Consult the linked 3M documents for complete, current technical and warranty terms.

This guide is provided by Guardian Bastille, LLC for reference during specification and bidding. It does not modify or supersede 3M's published technical or warranty terms. Guardian Bastille is a 3M Prestige Dealer; this document does not represent 3M certification of any project.